



PHONE

TABLET

COMPUTER

PERIPHERAL

COMMERCIAL

SERVICE

PCE-AC68

Network Standard IEEE 802.11a/b/g/n/ac

Interface PCI Express

Antenna 3 x R SMA Antenna

Operating Frequency 2.4GHz/5GHz

Operation Channel 11 for N. America, 13 Europe (ETSI)

Product Segment AC1900 ultimate AC performance: 600+1300Mbps

Data Rate 802.11 b/g/n/ac : downlink up to 1300Mbps, uplink up to 1300Mbps (20/40/80MHz)

Output Power ac mode : 18 ~22 dBm
b mode : 22 dBm
g mode : 19 ~22 dBm
n mode : 18 ~22 dBm

Modulation 64QAM, 16QAM, CCK, DQPSK, DBPSK, OFDM

Management Wireless configuration
connection management
connection profile setup

Security 64-bit WEP, 128-bit WEP, WPA2-PSK, WPA-PSK

Certificates CE, FCC, IC

Dimensions 103.3 x 68.9 x 21 mm (WxDxH)

Weight

125 g (Device Only)

Environmental Operating Temperature: 0 °C to 40 °C (°F to °F)
Storage Temperature: -20 ° to 65 ° C (°F to °F)
Operating Humidity: 10 % to 90 % (Non-condensing)
Storage Humidity: 10 % to 90 % (Non-condensing)

OS Support Windows® 8.1 , 32bit/64bit
Windows® 8 , 32bit/64bit
Windows® 7 , 32bit/64bit
Windows® Vista , 32bit/64bit
Windows® XP , 32bit/64bit

Package Content Dipole Antenna x 3
External magnetic antenna base
Low Profile Bracket
Support CD
Warranty card
Wireless LAN Adapter

Want More?

Tech In Style

ROG

SonicMaster

Asus Design Center

Eee Is Me

ZENBOOK

TUF

ASUS@vibe+

Who We Are

Awards

News

About ASUS

Investor Relations

Employment

About CSR

Press Room

Need Help?

Check Repair Status

Find Service Locations

Product Registration

Email Us

Call Us

Monday to Friday from 9:00
to 18:00

Community

