

ASUS VP279HE

178° Ultra-wide View with Eye Care Monitor



Key Features



Low Blue Light
& Flicker Free



IPS technology panel is optimized for the finest image and color quality with 178° wide-viewing-angle



Eliminate ghosting, allowing you to smoothly react your game



Decimating blurry to gain the upper hand in current video games



Exclusive GamePlus function provides the accurate and perfect gaming experience



Exclusive QuickFit technology enhance editing scenario



Extensive connectivity with HDMI ports for incredible home-theater entertainment



Flicker-free

To eliminate the disturbing flickers on screen to reduce eye fatigue



Ultra-low
Blue Light

You could choose from 4 levels of Ultra-low Blue Light modes for your best viewing and users scenario



Wall Mountable

Compatible with VESA wall-mount standard



Specification

Display	Panel Size : Wide Screen 27-inch (68.5 cm) LED backlight, 16:9 Display Viewing Area (HxV) : 597.888 x 336.312 mm Panel Type : WLED / IPS True Resolution : Full HD 1920 x 1080 Pixel Pitch : 0.311 mm Brightness(Max) : 250 cd/m² Contrast Ratio : 1,000:1 ASUS Smart Contrast Ratio (ASCR) : 100,000,000:1 Viewing Angle (CR≥10) : 178°(H)/178°(V) Color Saturation : 72% NTSC Response Time : 1ms MPRT Display Colors : 16.7M FlickerFree : Yes	
Video Feature	Blue Light Filter : Yes Trace Free Technology : Yes SPLENDID Video Intelligence Technology : Yes SPLENDID Video Preset Modes : 8 Modes (Standard / Scenery / Night View / Game / Theater / sRGB / Reading / Darkroom) Color Temperature Selection : 4 Modes (Cool / Normal / Warm / User) Skin-Tone Selection : 3 mode HDCP support: Yes GamePlus : Yes (Crosshair / Timer / FPS Counter / Display Alignment) QuickFit: 3 modes (Alignment Grid / Document / Photo) Adaptive-Sync/FreeSync™ : 48 – 75Hz	
I/O Ports	Signal Input : HDMI (v1.4) x 1 D-sub x 1	Earphone Jack : 3.5mm Mini Jack HDMI D-sub (VGA) 
Signal Frequency	Analog Signal Frequency : 24~83 KHz(H)/ 48~75 Hz(V) Digital Signal Frequency : 24~83 KHz(H)/ 48~75 Hz(V)	
Power Consumption	Power on (Typical) : <16.58W * Power Saving Mode : < 0.5W Power Off Mode : <0.5W Voltage : 100-240V, 50 / 60Hz	
Mechanical Design	Chassis Colors : Black Tilt : -5° ~ 20° VESA Wall Mount (100x100 mm)	
Security	Kensington lock	
Dimensions	Phys. Dimension with Stand (WxHxD) : 613.34 x 433.44 x 219.42 mm Phys. Dimension without Stand (WxHxD) : 613.34 x 365.31 x 50.03 mm Box Dimension (WxHxD) : 683 x 499 x 143 mm	
Weight	Net Weight (Esti.) : 4.34 kg Net Weight without Stand (For VESA Wall Mount) (Esti.) : 3.68 kg Gross Weight (Esti.) : 6.9 kg	
Accessories	Power Cord, HDMI cable (optional), VGA cable (optional), Warranty card, Quick Start Guide	
Compliance Standard	UL/cUL, CB, CE, ErP, EU Energy label, FCC, ICES-3, CCC, CEL, ISO9241-307, BSMI, CU, C-Tick, MEPS, VCCI, PSE, J-MOSS, KC, KCC, e-Standby, RoHS, Windows 7&8.1&10 WHQL, Energy Star®, EPEAT Bronze, TCO 8.0, TÜV-Flicker free, TÜV-Low Blue Light, WEEE, TUV-GS, TUV-Ergo	

*measuring a screen brightness of 200 nits without audio / USB / Card reader connection
*All specifications are subject to change without notice.

